

ABS/USCG A60 8 Man Linkable Sleeper

CERTIFIED LINKABLE SLEEPER FOR SAFE AREAS

Certifications

ABS
USCG
IMO/SOLAS

Single Side Connection

All essential services connections located on a single side.

Reduce Installation Cost

Plug and play connection for PA/GA, Fire & Gas detection, power, data.

A60/H60/H120 Available

Built to highest level of structural fire protection.



ISO

ISO connectors for easy stacking and securing.

Multiple AC Systems

Multiple oversized AC units for redundancy.

Blast Rated

Up to 500mbar available - custom blast ratings can be achieved.

Fire Safety

Standard fire detection and PA/GA in each module with optional gas detection.

HB Rentals' 40' ABS/USCG A60 Sleeper can accommodate up to 8 individuals. The module brings easy plug and play connections with safe, quick installation features. Superior engineering and construction allow our modules to stack in a variety of configurations, depending on host installation requirements.

Certifications:

- US Coast Guard 46CFR Subchapters I, I-A, L, SOLAS
- Class I/Div I & Class I/Div II Capable
- ABS Guide for Portable Accommodation Modules
- ABS Rules for Building and Classing Offshore Installations
- ABS Guide for Building and Classing Floating Production Installations
- ABS Rules for Building and Classing Mobile Offshore Drilling Units
- Rules for Building and Classing Steel Vessels
- Rules for Building and Classing Steel Vessels Under 90 Meters (295 feet) in Length
- Rules for Building and Classing Steel Barges
- IMO/SOLAS

Tested

- BS EN 12079
- DNV 2.7-1

Increased Worker Comfort

- Each bunk is equipped with black-out privacy curtains, bunk lights and outlets.
- Individual lockers for all personnel.
- Bedrooms equipped with desk and file cabinets.
- Linkable modules allow for PLQ replication on TLQ.
- Wet area designed with 2 separated sinks.

Robust Climate Control System

- 2 Oversized AC Systems – AC systems are independently controlled and provide AC airflow to the entire module.
- Split System – Easy maintenance with split condenser and air handler.

Robust Climate Control System (cont.)

- Independent Systems - Electrical disconnects allow for individual unit maintenance.

Superior Interior Construction

- Interlocking wall panel and ceiling design to decrease permeability.
- Easy maintenance material to facilitate house cleaning.

Superior Engineering and Construction

- Stackable design suitable for fixed and floating platforms, barges, vessels.
- True to dimension laydown footprint.
- Linkable design allows for separation of day/night shift.

Maximize Worker Safety

- A60 fire rated and optional H60/H120 fire rated construction.
- Up to 500 mbar blast rating available-custom rating can be achieved.
- 2 automatic fire dampeners.
- Standard fire detection and PA/GA in each module.
- Optional gas detection - LEL, H₂S, CO.
- Optional alarm integration to host vessel.
- 4-side egress – exits on all sides.

Designed for Safe and Easy Deployment

- Twist lock installation reduces installation.
- Stab-in-tube installation for easy porch/walkway installation.
- Single side essential services connections simplifies installation.
- Recessed ends mitigate risk of injuries and accidents.
- Optional black and grey water separation.
- Separate saltwater and potable water connections.
- Plug & Play connections for PA/GA, Fire & Gas detection, power, data, for reduced offshore set up time and reduced costs.

Fire Extinguisher




Gas Detection



Fire Alarm



Overview Layout



1 PLAN VIEW: GENERAL ARRANGEMENT

Specifications

Dimensions/Weights:

40'L x 10'W x 10'H
42,000 lbs.

Structure:

- ABS Guide for Portable Accommodation Modules
- ABS Rules for Building and Classing Offshore Installations
- ABS Guide for Building and Classing Floating Production Installations

- ABS Rules for Building and Classing Mobile Offshore Drilling Units
- Rules for Building and Classing Steel Vessels
- Rules for Building and Classing Steel Vessels Under 90 Meters (295 feet) in Length
- Rules for Building and Classing Steel Barges

Transportation:

- Fitted with ISO connectors
- Pad eyes for single point lift-meets ALL stringent ABS/

USCG structural requirements

Bulkheads:

- Fire Rating: A60
- Optional H60, H120

Fire & Gas:

- F&G Detection
- F&G Alarm (Optional)

Fire Damper:

Electro-Mechanical Actuation

Protection System:

Exterior Class I/Div II Available

Power Requirements:

3 Ph
480V 60A 60Hz
45 KVA Transformer

Climate Control:

1 AC System/Bedroom

more info at www.hbrentals.com

Regional Offices

Corporate Headquarters

5813 Highway 90 East
Broussard, LA 70518 USA
Tel +1 337 839 1641
Toll Free 800 262 6790

Americas Corporate Sales

11330 Clay Road
Ste 200
Houston, TX 77041 USA
Tel +1 281 999 0047
Tel +1 281 999 0047
Fax +1 281 999 6505
Toll Free 866 999 0040

Europe, Middle East Africa, Asia-Pacific

Howe Moss Drive
Kirkhill Industrial Estate,
Dyce, Aberdeen, AB21 OGL
Tel +44 1224 772304
Tel +44 1224 772641
Fax: +44 1224 772641

Offshore Operating & Service Facilities

Aberdeen, UK

Europe, Middle East, Africa, Asia-Pacific Support

Broussard, USA

Main Operating Facility

Trinidad and Tobago

Ciudad del Carmen, Mexico

Global Markets

Asia-Pacific
Europe
Middle East
Mexico
Trinidad and Tobago
United States/
Canada